



s.114 NPT

1/2" - 4" heavy pattern gate valve





# Quality

- Suitable for water-works, domestic and agricultural installations
- Non rising stem suitable to most difficult applications

#### Body

- Low pressure drop
- Finely cast sand blasted heavy brass body

#### Stem

• High performance PTFE stem seal

### **Threads**

• NPT female by female taper threads



## Handle

- Strong cast aluminum hand-wheel
- WARNING: do not exceed reasonable temperature and/or electrical load

#### Working pressure & temperature

- 200 PSI non-shock cold working pressure
- -4°F to +350°F
- **WARNING:** freezing of the fluid in the installation may severely damage the valve


## **Options**

• S.115 solder end connections


# Approved by or in compliance with

- GOST-R (Russia)
- **NOTE:** approvals apply to specific configurations/sizes only.





	Part description	Q.ty	Material		
1	Body	1	CW617N		
2	Gate	1	CW617N		
3	Stem	1	CW617N		
4	Body cap sealing	1	PTFE		
5	Сар	1	CW617N		
6	Stem ring	Stem ring 1 C			
7	Packing gland seal	1	PTFE		
8	Packing gland	1	CW617N		
9	Packing gland nut	1	CW617N		
10	Red round handle	Red round handle 1 Steel			
11	Disc	Disc 1 Aluminum			
12	Handle nut	1	CW617N		



С	Code	114D41	114E41	114F41	114G41	114H41	114 41	114L41	114M41	114N41
D	(inch)	1/2	3/4	1	1 <sup>1/4</sup>	1 1/2	2	2 1/2	3	4
DN	(inch)	0.504	0.669	0.827	1.063	1.339	1.772	2.205	2.667	3.543
Ι	(inch)	0.449	0.492	0.559	0.657	0.669	0.728	0.925	1.004	1.181
L	(inch)	1.693	1.772	2.047	2.323	2.480	2.716	3.465	3.740	4.488
А	(inch)	2.165	2.165	2.362	2.835	2.835	3.150	3.937	4.331	5.118
Н	(inch)	2.795	2.992	3.445	4.055	4.475	5.256	6.437	7.480	9.252
F	PSI	200	200	200	200	200	200	200	200	200

WARNING: This product can expose you to chemicals including lead which is known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

XCE114 - 4266