



s.112 NPT

1/2" - 4"
gate valve



Quality

- Suitable for water-works, domestic and agricultural installations
- Non rising stem suitable to most difficult applications

Body

- Hot forged sand blasted brass body
- Low pressure drop

Handle

- Red coated steel hand-wheel
- **WARNING:** do not exceed reasonable temperature and/or electrical load
- Zinc plated steel top nut

Threads


- NPT female by female taper threads

Stem


- High performance EPDM stem seal

Working pressure & temperature

- 150 PSI non-shock cold working pressure
- +14°F to +176°F (-10°C to +80°C)
- **WARNING:** freezing of the fluid in the installation may severely damage the valve



Part description	Q.ty	Material
1 Body	1	CW617N
2 Gate	1	CB 754S
3 Stem	1	CW614N
4 Body cap sealing	1	Guarnital Fibre
5 Cap	1	CW617N
6 Stem ring	1	CW614N
7 Packing gland seal	1	EPDM90
8 Packing gland	1	CW614N
9 Packing gland nut	1	CW614N
10 Red round handle	1	Steel
11 Handle nut	1	Steel



Code	112D00	112E00	112F00	112G00	112H00	112I00	112L00	112M00	112N00
D (inch)	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
DN (inch)	0.531	0.610	0.748	1.062	1.299	1.732	1.850	2.362	2.834
I (inch)	0.354	0.354	0.393	0.393	0.433	0.472	0.511	0.511	0.590
L (inch)	1.377	1.535	1.692	1.889	2.125	2.283	2.480	2.755	3.149
A (inch)	1.771	1.771	1.968	2.165	2.362	2.755	3.149	3.937	3.937
H (inch)	2.677	2.677	3.149	3.385	4.212	5.275	5.629	6.889	7.952

WARNING: This product can expose you to chemicals including lead which is known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

XCE112 - 4787

RuB, Inc. - www.rubinc.com